



Westex® DH Air™, made with Lenzing™ Lyocell, Modacrylic and Aramid fibers, brings all of the great characteristics you've come to love from Westex® DH, to a lightweight, Cat 2 fabric.



Excellent Performance Characteristics:



5.5 oz/yd²



Dual Hazard Protection



Breathability



Moisture Wicking



Color Consistency



The information in this publication is based on testing conducted by or conducted on behalf of Westex, Inc., a subsidiary of Milliken & Company, and represents our analysis of the test results. It is not intended to substitute for any testing that may be unique and necessary for your facility for you to determine the suitability of our products for your particular purpose. Since we cannot anticipate all variations in enduser conditions, Westex, Inc., makes no warranties and assumes no liability whatsoever in connection with any use of this information. As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/ labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Any test results reported are based on standard laboratory testing but should not be used to predict performance in actual fire situations. Each customer must test and be responsible for their own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/ different terms are rejected) unless explicitly agreed otherwise in a signed writing. Use caution near sources of flame or intense heat and do not launder with bleach of abric softeners. Chart data is based on random sampling from fabrics available in the marketplace. Westex® and Milliken® are registered trademarks of Milliken & Company. DH Air™ is a trademark of Milliken & Company. Lenzing is a trademark of Lenzing AG.